

Optics	<input type="checkbox"/> Transmission	<input type="checkbox"/> Transflection	
Flange Dimension	<input type="checkbox"/> DN25	<input type="checkbox"/> DN50	Other:
	<input type="checkbox"/> ANSI 1"	<input type="checkbox"/> ANSI 2"	Other:
Flange Facing	<input type="checkbox"/> Form A	<input type="checkbox"/> Form B1	Other:
Immersion Depth	mm (Probe tip to flange bottom edge)		
Operating Temperature	Min °C	Max °C	
Operating Pressure	Min bar	Max bar	
Materials (in contact with)	<input type="checkbox"/> 1.4571	<input type="checkbox"/> 1.4404	<input type="checkbox"/> 1.4410
	<input type="checkbox"/> Hastelloy C4	<input type="checkbox"/> Hastelloy C22	Other:
Seals (in contact with)	<input type="checkbox"/> Hastelloy C276	<input type="checkbox"/> Hastelloy C22	Other:
Process Window (in contact with)	<input type="checkbox"/> Sapphire	<input type="checkbox"/> Quartz	Other:
Optical Path Length	<input type="checkbox"/> 1mm	<input type="checkbox"/> 2mm	<input type="checkbox"/> 5mm
	Other:		
Collimator	<input type="checkbox"/> NIR range	<input type="checkbox"/> UV-VIS range	Other:
Optical Fiber (Installed in the probe)	<input type="checkbox"/> NIR range	<input type="checkbox"/> UV-VIS range	Other:
Name:			